

# Touch POS Terminal TL-150HX

**15" Solid Aluminum Alloy Stand**  
**Capacitive True Flat Touch TFT-LCD with LED Backlight Screen**  
**Best Performance with Intel Celeron J1900 or i3, i5**



## TL-150HX Specifications

Screen	15"(4:3) HD Color TFT-LCD,LED Backlight with Capacitive Touch Resolution :1024x768(RGB),XGA, Brightness :350cd/m2
CPU	Intel Celeron J1900 2.00 -2.42GHz Cache 2MB Quad-core; Option: i3 & i5 available
Memory	RAM DDR3 4GB *(8GB as option) , mSATA SSD 64GB *(SSD128GB/256GB as option)
OS/Power Supply	Windows 7/8/10*(Linux as option) Power supply: AC 100-240V/1.5A, Output DC12V 5A
In/Out Ports	USB2.0 x5 , USB3.0 x1, COM 232C x2, VGAX1, RJ45 LAN 10/100/1000 Mbps, Audio: x 1, Power DC-IN 12V x1
Second Display (option)	VFD 2x20 line Customer Display or 11.6 inch LCD Screen without Touch
Dimension / Net Weight	356 (W) x 348 (H) x 205-250 (D) (mm) / Net Weight: 4.6kg
Environment	Operating temperature: 0°C - 50°C, Storage temperature: -20°C -70°C
Other Option	i-Button Dallas Key with MSR, MSR, Wi-Fi