

All-in-one True Flat Touch POS Terminal TL-170X

17" Capacitive Touch Screen with Perfect Material Combination of Aluminum Alloy and Plastic POS Terminal



TL-170X Specifications

Screen	17"(4:3) BOE DV170XOM-N10 TFT LCD,LED Backlight with Capacitive Touch Resolution :1280x1024(RGB),XGA , Brightness :250cd/m2
CPU	Intel Celeron J1900 2.00 -2.42GHz Cache 2MB Quad-core
Memory	RAM DDR3 4GB *(8GB as option) , mSATA SSD 64GB *(SSD128GB/256GB as option)
OS/Power Supply	Windows 7/8/10*(Linux as option) Power supply: AC 100-240V/1.5A, Output DC12V 5A
In/Out Ports	USB2.0 x3 , USB3.0 x2, COM 232C x2, VGAX1, RJ45 LAN 10/100 Mbps, Audio: x 1 , DC Jack 12V ,line out 1 *(LAN 10/100/1000 as option)
Second Display (option)	VFD 20x2 line Customer Display
Dimension / Net Weight	375 (W) x 327(H) x 206~285 (D) (mm) / Net Weight: 5.4 Kg
Environment	Operating temperature: 0°C - 50°C, Storage temperature: -20°C - 70°C
Other Option	CPU i3, i5, Wi-Fi , MSR