

All-in-one True Flat Touch POS Terminal TL-156W

15.6" Capacitive Touch Screen with Easy Installation and Maintenance Back Cover POS Terminal



TL-156W Specifications

Screen	15.6"BOE NT 156WHM-N49 TFT LCD,LED Backlight with Capacitive Touch Resolution :1366x768(RGB), XGA , Brightness :220cd/m2
CPU	Intel Celeron J1900 2.00 -2.42GHz Cache 2MB Quad-core
Memory	RAM DDR3 4GB *(8GB as option) , mSATA SSD 64GB *(SSD128GB/256GB as option)
OS/Power Supply	Windows 7/8/10*(Linux as option) Power supply: AC 100-240V/1.5A, Output DC12V 5A
In/Out Ports	USB2.0 x5, USB3.0 x1, COM232x2, RJ45 LAN 10/100 Mbps, HDMI x 1 ,Audio x 1, DC Jack 12V *(LAN 10/100/1000 as option)
Second display (Option)	VFD 20x2 line Customer Display or 12.5" LCD Screen without Touch BOE NT125WHM-N42
Environment	Operating temperature: 0°C - 50°C, Storage temperature: -20°C - 70°C
Dimension/ Net Weight	388 (W) x 335 (H) x 195-240(D) mm Net Weight: 4.8kg
Other Option	Wi-Fi, MSR