

- TP Series True All in One Compact POS Terminal -

TCS TPA-116

For Retail and Hospitality



TPA-116x



TPA-116a

TCS TPA-116 Specification

Model	TPA-116x	TPA-116a
OS	Windows 8/10 & Linux (Option)	Android 7.1/8.1
CPU & RAM	Intel J1900 2.00-2.42GHz Cache 2MB, DDR3 4GB or J4125 2.00-2.70GHz, Cache 4MB, DDR4 4GB	Rock chip RK3288 Quad-Core DDR3 2GB
Storage	SSD 64GB as standard	8GB eMMC as standard, 16GB as option
Printer	80mm SEIKO Thermal Printer * Speed: 220 mm/sec with Auto Cutter or 58mm Thermal Printer * Speed: 90 mm/sec Multinational character set, Reliability printing: 100KM, Cutter life: 1 million times	
Main Display	11.6" Touch TFT Screen (WXGA resolution 1366 x 768 pixel) with Capacitive Touch Panel	
Customer Display (Option)	5" LCD Second Display without RFID, Barcode Scanner or VFD 2 x 20 character	
In/Out Ports	USB3.0 x 2, USB2.0 x 3, COM x 2, RJ45 LAN 10/100Mbps as standard, 10/100/1000Mbps as option, VGA x 1 RJ11/12, Audio	USB2.0 x 5, COM x 2, LAN 100/1000 Ethernet RJ45, RJ11/12, Audio out/input, TF card, Bluetooth, Wi-Fi as standard
Environment	Operating temperature and humidity : -10°C - 40°C, 20 - 80% Storage temperature and humidity : -20°C - 50°C, 20 - 90%	
Power Supply	Input: AC100-240V/1.5A Output: DC12V 5A	
Dimension/Weight	300 (W) x 316 (D) x 102(H) mm / Net Weight: 3.5kg	
Option	Customer Display, RFID, 2D Barcode Scanner, MSR, Wi-Fi for TPA-116x, 4G LTE for TPA-116x & TPA-116a	