

# All-in-one True Flat Touch POS Terminal TL-150H

**15" Capacitive Touch Screen with Easy Installation and Maintenance Back Cover POS Terminal**



## TL-150H Specifications

<b>Screen</b>	15"(4:3) BOE DV150XOM-N12 TFT LCD,LED Backlight with Capacitive Touch Resolution :1024x768(RGB),XGA , Brightness :350cd/m2
<b>CPU</b>	Intel Celeron J1900 2.00 -2.42GHz Cache 2MB Quad-core
<b>Memory</b>	RAM DDR3 4GB *(8GB as option) , mSATA SSD 64GB *(SSD128GB/256GB as option)
<b>OS/Power Supply</b>	Windows 7/8/10*(Linux as option) Power supply: AC 100-240V/1.5A, Output DC12V 5A
<b>In/Out Ports</b>	USB2.0 5 port, USB3.0 1 port, COM 232*2, RJ45 LAN 10/100 Mbps, HDMI: x 1 ,Audio: x 1 , DC Jack 12V *(LAN 10/100/1000 as option)
<b>Second Display (option)</b>	VFD 20x2 line Customer Display or 12.5" LCD Screen without Touch BOE NT125WHM-N42
<b>Dimension / Net Weight</b>	350 (W) x 357(H) x 190-250 (D) (mm) / Net Weight: 5.4 Kg
<b>Environment</b>	Operating temperature: 0°C - 50°C, Storage temperature: -20°C - 70°C
<b>Other Option</b>	Wi-Fi , MSR